

MARPOL® HDB 505G

High Density Polyethylene Copolymer

Marco Polo International, Inc.

Message:

MARPOL® HDB 505G is a high molecular weight high density polyethylene copolymer. It has a combination of excellent processability, melt strength, high impact strength, chemical resistance and high stress cracking resistance.

General Information			
Features	Copolymer		
	Good Chemical Resistance		
	Good Melt Strength		
	Good Processability		
	High ESCR (Stress Crack Resist.)		
	High Impact Resistance		
	High Molecular Weight		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm ³	ASTM D4883
Melt Mass-Flow Rate (MFR)			ASTM D1238
190°C/2.16 kg	< 0.10	g/10 min	
190°C/21.6 kg	5.5	g/10 min	
Environmental Stress-Cracking Resistance (100% Igepal)	> 1000	hr	ASTM D1693B
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	20.7	MPa	ASTM D638
Tensile Elongation (Break)	1100	%	ASTM D638
Flexural Modulus	1030	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Tensile Impact Strength (23°C)	420	kJ/m ²	ASTM D1822
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	< -76.1	°C	ASTM D746
Vicat Softening Temperature	127	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

