

Hy-Vin® VX332/1

Flexible Polyvinyl Chloride

INEOS Compounds

Message:

Hy-Vin® VX332/1 is a Flexible Polyvinyl Chloride material. It is available in Europe.

Important attributes of Hy-Vin® VX332/1 are:

Good Flexibility

Good Processability

General Information			
Features	General Purpose		
	Good Flexibility		
	Good Moldability		
Uses	General Purpose		
Appearance	Colors Available		
	Natural Color		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.33	g/cm ³	BS 2782
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A, 15 sec, 23°C)	69		BS 2782
BS Softness	53	°	BS 2782
Cold Flexibility	-28	°C	BS 2782
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹	12.7	MPa	BS 2782
Tensile Elongation ² (Break)	290	%	BS 2782
Extrusion	Nominal Value	Unit	
Cylinder Zone 1 Temp.	155	°C	
Cylinder Zone 2 Temp.	160	°C	
Cylinder Zone 3 Temp.	165	°C	
Die Temperature	170	°C	
NOTE			
1.	500 mm/min		
2.	500 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

