

Borealis PP WE950CF

Polyolefin

Borealis AG

Message:

WE950CF is a polyolefin resin suitable for the manufacturing of non-oriented sterilisable peelable cast films on chill roll processes.

CAS-No. 9010-79-1

CAS-No. 9002-88-4

General Information			
Additive	Antiblock (360 ppm) 2		
Features	Recyclable Material		
Uses	Film		
	Food Packaging		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ISO 1133
Optical	Nominal Value	Unit	Test Method
Haze			ASTM D1003
-- ¹	< 10	%	
-- ²	< 5.0	%	
Additional Information	Nominal Value	Unit	Test Method
Peel Force	200.0 to 600.0	N/m	Internal Method
NOTE			
1.	after sterilization		
2.	before sterilization		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT