

NEXT REGRIND PC/ABS MG10-300

Polycarbonate + ABS
NEXT Specialty Resins, Inc.

Message:

NEXT REGRIND PC/ABS MG10-300 is a Polycarbonate + ABS (PC+ABS) material. It is available in North America for injection molding. Important attributes of NEXT REGRIND PC/ABS MG10-300 are:

- Eco-Friendly/Green
- Good Processability
- Heat Resistant
- High Viscosity
- Impact Resistant

Typical applications include:

- Appliances
- Automotive
- Electrical/Electronic Applications

General Information			
Recycled Content	Yes		
Features	Good Processability		
	High Heat Resistance		
	High Impact Resistance		
	High Viscosity		
Uses	Appliances		
	Automotive Applications		
	Electrical/Electronic Applications		
Appearance	Black		
Forms	Regrind		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.13	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR)	3.0 to 5.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	110		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2070	MPa	ASTM D790
Tensile Strength	41.4	MPa	ASTM D638
Tensile Elongation (Break)	110	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	610	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	104	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

