# Small Boss HS-105-3

### Polyvinyl Chloride

#### Tongxiang Small Boss Special Plastic Products Co., Ltd.

#### Message:

PVC Granule Special for Cable, with PVC resin as its basic material and added with plasticizer, stabilizer and other additives, as well as mixed with high efficient flame retardant, PVC cable material special for network cable is processed through particular mixing refining device. It is a PVC cable material with high flame-retardant performance, which has excellent heat resistant and oxidation resistant properties. It can meet the thermal aging test request in UL Standard and mainly applies in network cable jacket with CMH, CMX, CM, CMG, CMR and CMP symbol of burning grade in UL13, UL444 and other standards. Meanwhile, it can also apply in cable jacket with high flame-retardant request.

General Information				
Additive	Flame Retardant			
Features	Fatigue Resistant			
Uses	Insulation			
	Wire & Cable Applications			
Wire Types	СМ			
	CMG			
	СМН			
	СМР			
	CMR			
	СМХ			
Agency Ratings	UL 13			
	UL 444			
Forms	Granules			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	< 1.40	g/cm³	ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	> 15.0	MPa	ASTM D638	
Tensile Elongation (Break)	> 150	%	ASTM D638	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-40.0	°C	ASTM D746	
Hot Deformation	< 40	%		
Thermal Stability (200°C)	> 1	hr		
Weight Loss on Heating <sup>1</sup> (100°C)	< 20	g/m²		
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity (20°C)	> 1.0E+14	ohms·cm	ASTM D257	
Dielectric Strength	> 20	kV/mm	ASTM D149	
Flammability	Nominal Value	Unit	Test Method	

Oxygen Index	> 30	%	ASTM D2863
NOTE			
1.	168 hr		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

