

Preformance® PET ES11(A)

Polyethylene Terephthalate

AlphaPet Inc.

Message:

PREFORMANCE® PET ES11(A) is a high intrinsic viscosity food grade PET copolymer specifically designed for the CSD container market. It offers enhanced reheat ability that improves productivity and energy savings during blow molding. PREFORMANCE® PET ES11(A) resin is considered safe for food packaging applications based upon compliance with FDA Regulation 21 CFR Section 177.1630 specifications.

General Information			
Features	Copolymer		
	Compliance of Food Exposure		
	Viscosity, High		
Uses	Container		
	Food packaging		
Agency Ratings	FDA 21 CFR 177.1630		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.85	g/cm ³	Internal method
Acetaldehyde		ppm	Internal method
Color b	-1.50		Internal method
Color L	> 70.0		Internal method
Intrinsic Viscosity	0.84	dl/g	Internal method
Water content-as packed		wt%	Internal method
Black Specks	None		Internal method
Dust - as packed		ppm	Internal method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT