

Sumiliteresin® PR-3500 I

Phenolic

SBHPP

Message:

SUMILITERESIN® PR-3500 I is a liquid straight resol phenolic resin, water base. It is generally apply as binder of inorganic fiber such as rockwool & glasswool.

Characteristics

SUMILITERESIN® PR-3500 I is preferable to use for rockwool & glasswool manufacturing. It is easy diluted with water in spraying process. By use this resin, It will be good strength, easy handling and low emmision.

General Information		
Features	Low volatilization	
	Good strength	
Uses	Adhesive	
Appearance	Red	
Forms	Liquid	
Physical	Nominal Value	
pH (25°C)	7.0 - 8.6	
Resin Content - 135°C/1h	48 - 54	%
Uncured Properties	Nominal Value	Unit
Density (25°C)	1.16 - 1.18	g/cm ³
Viscosity (25°C)	0.032 - 0.052	Pa·s
Gel Time (150°C)	2.5 - 3.3	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT