# Solprene® 1217

### Solution Styrene Butadiene Rubber

### **Dynasol Elastomers**

### Message:

Solprene1217 is a linear random-block styrene/butadiene copolymer having 25% of styrene content, 17.5% present as a polystyrene block. It has a non-staining antioxidant system, BHT/TNPP free, FDA approved for use in food contact applications and is essentially gel free with a very clear color.

Solprene 1217 is used as compounding ingredient for adhesives, as modifier for thermoplastic resins. It is an excellent asphalt modifier or, for formulation of caulks and sealants; it is also an excellent processing aid for most polymers, giving good low temperature resistance. Used in extruded goods, soles, and heels.

It is available in bales wrapped in low melting point polyethylene.

General Information				
Additive	Antioxidant			
Features	Antioxidant			
	BHT Free			
	Food Contact Acceptable			
	High Clarity			
	Linear Polymer Structure			
	Low Gel			
	Low Temperature Resistant			
	Random Copolymer			
Uses	Adhesives			
	Asphalt Modification			
	Footwear			
	Plastics Modification			
Agency Ratings	FDA Food Contact, Unspecified Rating			
Appearance	Clear/Transparent			
Forms	Bale			
Processing Method	Extrusion			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.928	g/cm³	DIN 53479	
Mooney Viscosity (ML 1+4, 100°C)	47	MU	ASTM D1646	
Block Styrene <sup>1</sup>	18	%		
Color - Apha <sup>2</sup>	< 15			
Solution Viscosity - 30% in toluene <sup>3</sup>	4.0	Pa·s		
Styrene Content	25	%	ASTM D5775	
Volatile Matter <sup>4</sup>	< 0.75	%		
Insolubles <sup>5</sup>	< 0.10	%		
NOTE				

1.	NM 202-07	
2.	NM 300-33	
3.	NM 300-18	
4.	NM 300-01	
5.	NM 300-15	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

