# Zhongfa PP ZF-UV1

### Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

#### Message:

Zhongfa PP ZF-UV1 is a polypropylene material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP ZF-UV1 are: high gloss Good UV resistance chemical resistance UV stability The typical application field of Zhongfa PP ZF-UV1 is: automotive industry

Additive Features	UV stabilizer Highlight Good UV resistance			
Features	Good UV resistance			
	Good liquidity			
	Good chemical resistance			
Uses	Application in Automobile Field			
Forms	Particle			
Processing Method	Injection molding			
Physical N	Nominal Value	Unit	Test Method	
Specific Gravity 0	0.910	g/cm <sup>3</sup>	ASTM D792	
Melt Mass-Flow Rate (MFR)	3.0	g/10 min	ASTM D1238	
Molding Shrinkage - Flow 1	1.8	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	98		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength 3	35.0	MPa	ASTM D638	
Tensile Elongation (Break) 1	100	%	ASTM D638	
Flexural Modulus 1	1400	MPa	ASTM D790	
Flexural Strength 3	38.0	MPa	ASTM D790	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0.45 MPa, Unannealed) 1	120	°C	ASTM D648	
Additional Information				
Aging Resistance at 150°C: >350 hrNotched Izod Impact, ASTM D256: 3.5 kJ/m <sup>2</sup> Unnotched Izod Impact, ASTM D256: No Break				
Injection	Nominal Value	Unit		
Drying Temperature S	90.0 - 95.0	°C		
Drying Time 2	2.0 - 3.0	hr		
Processing (Melt) Temp 1	195 - 225	°C		

Mold Temperature	45.0 - 80.0	°C
Injection Pressure	60.0 - 90.0	MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

