ISOTHANE® 1160D

Thermoplastic Polyurethane Elastomer (Polyester)

Great Eastern Resins Industrial Co Ltd (GRECO)

Message:

ISOTHANE 1100series products are polyester poly(adipate)ester based thermoplastic polyurethanes. They exhibit good toughness, solvent resistance, easy processing, and high transparency. These products can be injection molded, and extruded.

Suggested Applications

Seals, Gaskets, Sheets, Tube, Cable, Shoe Sole, Sporting Equipments and Mechanical Goods.

General Information					
Features	General Purpose				
	Good Processability				
	Good Toughness				
	Solvent Resistant				
Uses	Cable Jacketing				
	Footwear				
	Gaskets				
	General Purpose				
	Machine/Mechanical Parts				
	Seals				
	Sheet				
	Sporting Goods				
	Tubing				
Appearance	Clear/Transparent				
Processing Method	Extrusion				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.21	g/cm³	ASTM D792		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D)	58		ASTM D2240		
Mechanical	Nominal Value	Unit	Test Method		
Taber Abrasion Resistance (H-22 Wheel)	60.0	mg	ASTM D1044		
Elastomers	Nominal Value	Unit	Test Method		
Tensile Stress			ASTM D412		
50% Strain	15.0	MPa			
100% Strain	19.0	MPa			
300% Strain	33.0	MPa			
Tensile Strength (Yield)	40.0	MPa	ASTM D412		

Tensile Elongation (Break)	480	%	ASTM D412
Tear Strength ¹	200	kN/m	ASTM D624
NOTE			
1.	Die C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

