

Durez® 33768

Phenolic

Sumitomo Bakelite North America, Inc.

Message:

Durez 33768 is a modified two-step, powdered phenolic resin.

Durez 33768 is recommended for use in Friction Applications, Bonded Abrasive Applications, any application requiring enhanced thermal resistance.

Durez 33768 is modified to give thermal resistance on the finished product.

General Information			
Features	Bondability		
	High Heat Resistance		
Uses	Bonding		
Forms	Powder		
Thermoset	Nominal Value	Unit	Test Method
Post Cure Time (150°C)	0.033	hr	
Additional Information	Nominal Value	Unit	Test Method
Hexa	6.8	%	Internal Method
Inclined Plate Flow (125°C)	2.50	cm	Internal Method
Screen Mesh ¹	11	%	Internal Method
NOTE			
1.	325 Mesh		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT