

POLYPRO® RJ6428

Polypropylene Random Copolymer

YUHWA Korea Petrochemical Ind. Co., Ltd.

Message:

POLYPRO® RJ6428 is a Polypropylene Random Copolymer (PP Random Copolymer) material. It is available in Asia Pacific for injection molding.

Important attributes of POLYPRO® RJ6428 are:

RoHS Compliant

Clarity

Copolymer

High Flow

Impact Resistant

Typical applications include:

Business/Office Goods

Coating Applications

Containers

Food Contact Applications

General Information			
Features	Good Impact Resistance		
	High Clarity		
	High Flow		
	Random Copolymer		
Uses	Containers		
	Protective Coverings		
	Stationary Supplies		
Agency Ratings	FDA Food Contact, Unspecified Rating		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	28	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	90		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	32.4	MPa	ASTM D638
Tensile Elongation (Break)	> 500	%	ASTM D638
Flexural Modulus	1180	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	59	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT