

Vinnolit® EP 7060

Polyvinyl Chloride Homopolymer

Vinnolit GmbH & Co. KG

Message:

Vinnolit EP 7060 is a medium molecular weight emulsion type PVC homopolymer with a medium-high emulsifier content. It produces plastisols exhibiting medium viscosity and yield value at low shear rates with pronounced pseudoplastic flow properties at high shear rates with medium-high plasticizer levels (70-100 phr). This grade can be used in blends to generally increase low shear viscosity and reduce dilatancy. It gives good thermal stability with a wide range of stabiliser types. The use of high speed type mixers is recommended.

General Information			
Features	Medium Molecular Weight		
Uses	Blending		
Agency Ratings	EC 1907/2006 (REACH)		
Processing Method	Plastisol		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.48	g/cm ³	ISO 60
K-Value	70.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	124.0	ml/g	ISO 1628
Emulsifier Content	Medium		
Particle Size Distribution ¹	< 1.0	%	ISO 4610
Volatile Matter	< 0.30	%	ISO 1269
NOTE			

1. retained on 0.063 mm screen

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT