

YUCLAIR® MM810

High Density Polyethylene
SK Global Chemical

Message:

YUCLAIR® MM810 is a High Density Polyethylene product. It is available in Asia Pacific, Europe, or North America. Typical application: Fabrics/Fibers.
Characteristics include:
Good Adhesion
Good Processability

General Information			
Features	Good Adhesion		
	Good Processability		
Uses	Fibers		
Physical	Nominal Value	Unit	Test Method
Density	0.954	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	30	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.5	MPa	ASTM D638
Flexural Modulus	883	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT