

# MIDILENA III HDPE 5000S

High Density Polyethylene

ROMPETROL PETROCHEMICALS S.R.L.

## Message:

MIDILENA III HDPE 5000S is a High Density Polyethylene product. It can be processed by extrusion and is available in Europe. Applications of MIDILENA III HDPE 5000S include fabrics/fibers and straps/ropes. Primary characteristic: antioxidant.

General Information			
Additive	Antioxidant		
	Halogen		
Features	Antioxidant		
	Halogenated		
Uses	Fibers		
	Rope		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.85	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT