

Ethylplus CO 125

Polyethylene
Fainplast Compounds S.r.l

Message:

Ethylplus CO 125 is a Polyethylene product. It is available in Africa & Middle East, Europe, Latin America, or North America. Typical application: Wire & Cable.

Characteristics include:

Flame Retardant

Crosslinkable

General Information			
Additive	Flame Retardant		
Features	Crosslinkable		
	Flame Retardant		
	Halogenated		
Uses	Insulation		
	Wire & Cable Applications		
Agency Ratings	UL 1581		
Physical	Nominal Value	Unit	Test Method
Density	1.37	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, 15 sec)	37		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	15.0	MPa	ISO 527-2
Tensile Strain (Break)	600	%	ISO 527-2
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (20°C)	1.0E+15	ohms · cm	IEC 60093
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	27	%	ISO 4589-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT