Braskem PP DH765.01

Polypropylene Homopolymer

Braskem Europe GmbH

Message:

BRASKEM DH765.01 Polypropylene Resin is a homopolymer Polypropylene for medium to higher flow Injection Molding applications. The resin has a very good balance of physical properties and excellent organoleptic. BRASKEM DH765.01 Polypropylene Resin is nucleated and contains a very efficient antistatic package offering good optical properties (transparency). It is designed and formulated to allow for very easy processing, short cycle times, low shrinkage and good part dimensional stability.

Applications:

Rigid packaging e.g. cosmetics, caps & closures Consumer goods e.g. housewares, general appliances

Process:

Injection Molding

General Information				
Additive	Nucleating agent			
	Antistatic property			
Features	Excellent Organoleptic Properties			
	Nucleated			
	Good dimensional stability			
	Optical			
	Homopolymer			
	Antistatic property			
	Workability, good			
	Fast molding cycle			
	Medium liquidity			
	Definition, high			
	Low shrinkage			
Uses	Cosmetic Packaging			
	Packaging			
	Electrical appliances			
	Shield			
	Household goods			
	Shell			
	Consumer goods application field			
	Hard packaging			
Agency Ratings	FDA 21 CFR 177.1520(c) 1.1			
	Europe 10/1/2011 12:00:00 AM			
Processing Method	Injection molding			

Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm³	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	25	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (Injection Molded)	1650	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C, Injection Molded)	3.5	kJ/m²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

