Huafon JF-W-3045

Polyurethane

Huafon Group Co., Ltd.

Message:

General Type Characteristics Mid soft type, good property of embossing, uniform cell structure, nonstick surface. Applications Shoes, Bags

| General Information | | | |
|-------------------------------|---------------|------|--|
| Features | Non-Stick | | |
| | Soft | | |
| | | | |
| Uses | Bags | | |
| | Footwear | | |
| | | | |
| Additional Information | Nominal Value | Unit | |
| Solvents | DMF | | |
| Uncured Properties | Nominal Value | Unit | |
| Solids Content | 29 to 31 | % | |
| Viscosity (25°C) | 160 to 260 | Pa·s | |
| Cured Properties | Nominal Value | Unit | |
| Tensile Modulus (100% Secant) | 4.00 to 5.00 | MPa | |
| Tensile Strength | > 35.0 | MPa | |
| Tensile Elongation at Break | > 550 | % | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

