

SWANCOR Epoxy 917

Epoxy; Epoxide
SWANCOR IND. CO., LTD.

Message:

Vinyl ester primer for both metal and concrete.
Excellent adhesion to both metal and concrete.
Excellent heat resistance and chemical resistance

| General Information | | | |
|--|--------------------------|------|-------------|
| Features | Good Adhesion | | |
| | Good Chemical Resistance | | |
| | High Heat Resistance | | |
| Appearance | Clear Amber | | |
| Forms | Liquid | | |
| Thermal | Nominal Value | Unit | Test Method |
| Deflection Temperature Under Load (0.45 MPa, Unannealed) | 145 | °C | ASTM D648 |
| Thermoset | Nominal Value | Unit | Test Method |
| Shelf Life (25°C) | 13 | wk | |
| Thermoset Mix Viscosity (25°C) | 425 | cP | ASTM D2393 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT