# Zhongfa PP ZF-ZR1

#### Polypropylene

Yuyao Zhongfa Engineering Plastics Co. Ltd.

#### Message:

Zhongfa PP ZF-ZR1 is a polypropylene material. This product is available in the Asia-Pacific region and is processed by injection molding. The main features of Zhongfa PP ZF-ZR1 are:

high gloss

chemical resistance

The typical application field of Zhongfa PP ZF-ZR1 is: automotive industry

General Information				
Features	Highlight			
	Good liquidity			
	Good chemical resistance			
Uses	Application in Automobil	Application in Automobile Field		
Forms	Particle	Particle		
Processing Method	Injection molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.910	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR)	3.5	g/10 min	ASTM D1238	
Molding Shrinkage - Flow	1.8	%	ASTM D955	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	67		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	35.0	МРа	ASTM D638	
Tensile Elongation (Break)	200	%	ASTM D638	
Flexural Modulus	1000	МРа	ASTM D790	
Flexural Strength	38.0	МРа	ASTM D790	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (				
MPa, Unannealed)	120	°C	ASTM D648	
Additional Information				
Aging Resistance at 150°C: >250 hrN			1 D256: No Break 	
Injection	Nominal Value	Unit		
Drying Temperature	90.0 - 95.0	°C		
Drying Time	2.0 - 3.0	hr		
Processing (Melt) Temp	195 - 225	°C		
Mold Temperature	45.0 - 80.0	°C		
Injection Pressure	60.0 - 90.0	MPa		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2