

Sylvin 9221-72 Black

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 9221-72 Black Is A Filled Vinyl Compound Formulated For Profile Extrusion And Injection Molding Applications.

General Information	
Filler / Reinforcement	Filler
Uses	Profiles
Appearance	Black
Processing Method	Injection Molding Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.33	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	72		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	10.7	MPa	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	43.8	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-38.0	°C	ASTM D746
Melting Temperature	160 to 171	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

