Hifax TYC 900X BLACK

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hifax TYC 900X BLACK is a 15% talc filled PP copolymer, with superior flowability, good impact/stiffness balance, excellent paintability and processability. The product is also available in black color, pellet form.

For regulatory compliance information, see Hifax TYC 900X BLACK Product Stewardship Bulletin (PSB) and Safety Data Sheet (SDS).

This grade is not intended for medical, pharmaceutical, food and drinking water applications.

General Information					
Filler / Reinforcement	Talc filler, 15% filler by weight				
Additive	Impact modifier				
Features	Good dimensional stability				
	Impact modification				
	Rigid, good				
	Copolymer				
	Impact resistance, good				
	Workability, good				
	Sprayable				
	High liquidity				
	Low temperature impact resistance				
	ductility				
	Excellent appearance				
Uses	Car anti-collision bar				
	Application in Automobile Field				
Appearance	Black				
Forms	Particle				
Processing Method	Injection molding				
Physical	Nominal Value	Unit	Test Method		
Density (23°C)	1.00	g/cm³	ISO 1183/A		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	23	g/10 min	ISO 1133		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Stress (Yield, 23°C)	18.0	MPa	ISO 527-2		
Flexural Modulus ¹ (23°C)	1550	MPa	ISO 178/A		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ISO 180/1A		
-20°C	6.0	kJ/m²	ISO 180/1A		
23°C	35	kJ/m²	ISO 180/1A		

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	95.0	°C	ISO 75-2/B
NOTE			
1.	1.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

