

MTEGRITY™ PP Impact Copolymer CP710

Polypropylene Impact Copolymer

M. Holland Company

Message:

MTEGRITY™ PP Impact Copolymer CP710 is a Polypropylene Impact Copolymer (PP Impact Copolymer) product. It can be processed by injection molding and is available in North America. Applications of MTEGRITY™ PP Impact Copolymer CP710 include caps/lids/closures, engineering/industrial parts and household applications.

Characteristics include:

- Antistatic
- Copolymer
- Impact Resistant
- Nucleated

General Information			
Additive	Antistatic		
	Nucleating Agent		
Features	Antistatic		
	Good Flow		
	Good Impact Resistance		
	Impact Copolymer		
	Nucleated		
Uses	Closures		
	Household Goods		
	Thin-walled Parts		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.901	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	35	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	24.5	MPa	ASTM D638
Tensile Elongation (Yield)	6.0	%	ASTM D638
Flexural Modulus	1170	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	110	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

