

Evermore PUR SS-1060G

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SS-1060G is a Polyurethane product. It is available in Asia Pacific. Typical application: Fabrics/Fibers.

Characteristics include:

Antiblock

Good Flexibility

High Gloss

| General Information | |
|---------------------|----------------------|
| Additive | Antiblock |
| Features | Aliphatic |
| | Antiblocking |
| | Good Flexibility |
| | High Gloss |
| | Medium Hardness |
| Uses | Synthetic Leather |
| | Textile Applications |

| Elastomers | Nominal Value | Unit | Test Method |
|------------------------------|---------------|------|-------------|
| Tensile Stress (100% Strain) | 4.90 to 6.86 | MPa | ASTM D412 |
| Tensile Strength (Yield) | 39.2 to 58.8 | MPa | ASTM D412 |
| Tensile Elongation (Break) | 450 to 700 | % | ASTM D412 |
| Fill Analysis | Nominal Value | Unit | Test Method |
| Melt Viscosity (25.0°C) | 60.0 to 80.0 | Pa·s | ASTM D3835 |
| Additional Information | Nominal Value | Unit | Test Method |
| Non-Volatile Content | 29 to 31 | % | |
| Solvents | DMF, MEK | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT