

SUMILITE® EL-3800F

Epoxy; Epoxide
Sumitomo Bakelite Co., Ltd.

Message:
SUMILITE®EL-3800F is an epoxy; Epoxy resin products. It is available in North America.

General Information			
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36	g/cm ³	ASTM D792
Water Absorption (Equilibrium, 23°C)	0.53	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (0.700 mm)	109		ASTM D785
Additional Information			


Flexural Strength @ Yield, ASTM D790, 0.7 mm, MD: 622 MPaFlexural Strength @ Yield, ASTM D790, 0.7 mm, TD: 289 MPaTensile Strength @ Yield, ASTM D638, 0.7 mm, MD: 148 MPaTensile Strength @ Yield, ASTM D638, 0.7 mm, TD: 131 MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT