

# Premier LD00319 - A

Low Density Polyethylene

Premier Polymers, LLC.

## Message:

Premier LD00319 is a low density fractional melt blown film resin suitable for heavy duty film requiring high strength and processability. Meets all requirements of the U.S. Food and Drug Administration as specified in 21 CFR 177.1520, covering safe use of polyolefin articles intended for direct food contact.

General Information			
Additive	High Antiblock		
Features	Food Contact Acceptable		
	High Antiblocking		
	Low Density		
Uses	Film		
Agency Ratings	FDA 21 CFR 177.1520		
Physical	Nominal Value	Unit	Test Method
Density	0.919	g/cm <sup>3</sup>	ASTM D4883
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.25	g/10 min	ASTM D1238
Films	Nominal Value	Unit	Test Method
Secant Modulus			ASTM D882
MD	193	MPa	
TD	241	MPa	
Tensile Strength			ASTM D882
MD : Break	25.5	MPa	
TD : Break	24.1	MPa	
Tensile Elongation			ASTM D882
MD : Break	150	%	
TD : Break	550	%	
Elmendorf Tear Strength			ASTM D1922
MD	300	g	
TD	150	g	
Optical	Nominal Value	Unit	Test Method
Haze	20	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

