

REPOL® T020MZ

Polypropylene

Reliance Industries Limited

Message:

REPOL Polypropylene T020MZ is manufactured using Unipol PP process which combines the production efficiency of gas phase fluidized bed reactor technology with the high activity stereospecific catalyst system. Repol T020MZ is recommended for use in Blow Moulding and Extrusion processes. It is an ideal material for making clear bottles, containers, ball pen refills, sheets, stationery items and thermoformed products.

General Information			
Features	Good Impact Resistance		
	Good Processability		
	High Clarity		
	High Gloss		
	Terpolymer		
Uses	Bottles		
	Containers		
	Sheet		
	Stationary Supplies		
	Writing Instruments		
Forms	Pellets		
Processing Method	Blow Molding		
	Extrusion		
	Thermoforming		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Yield)	28.0	MPa	ASTM D638
Tensile Elongation ² (Yield)	12	%	ASTM D638
Flexural Modulus - 1% Secant ³	1050	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	110	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	90.0	°C	ASTM D648
Melting Temperature	145	°C	DSC
NOTE			
1.	Type I, 50 mm/min		

2.	Type I, 50 mm/min
3.	Type I

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

