

Sylvin 8240-98FU White 1513

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:

Sylvin 8240-98FU White 1513 Is A Vinyl Compound Formulated For Outdoor Extrusion Applications. This Compound Contains An Antimicrobial At 2% And 5% Titanium Dioxide.

General Information			
Filler / Reinforcement	Titanium Dioxide,5.0% Filler by Weight		
Additive	Antimicrobial (Fungicide) (2%)		
Features	Microbe Resistant		
Uses	Outdoor Applications		
Appearance	White		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.52	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	98		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	20.0	MPa	ASTM D638
Tensile Elongation (Break)	200	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	131	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	177 to 191	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT