

# SUMILITE® PVC VSL-4610-N

Polyvinylidene Chloride

Sumitomo Bakelite Co., Ltd.

Message:

SUMILITE®PVC VSL-4610-N is a polyvinylidene chloride (PVDC) product. It is available in North America. SUMILITE®The application fields of PVC VSL-4610-N include thin plates and medical/health care.

Features include:

- Hard
- moisture resistance

General Information			
Features	Moisture resistance		
	Medium hardness		
Uses	Sheet		
	Drug		
Forms	Particle		
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD: Yield, 330 μm	37.2	MPa	ASTM D882
TD: Yield, 330 μm	33.3	MPa	ASTM D882
Tensile Elongation			ASTM D882
MD: Fracture, 330 μm	180	%	ASTM D882
TD: Fracture, 330 μm	180	%	ASTM D882
Water Vapor Transmission	0.27	g/m <sup>2</sup> /24 hr	ASTM E96
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	96.0	°C	ASTM D1525
Optical	Nominal Value	Unit	Test Method
Transmittance (330 μm)	85.0	%	ASTM D1003
Haze (330 μm)	5.0	%	ASTM D1003
Additional Information			

The values listed as ASTM D882 were tested in accordance with JIS K6734The value listed as ASTM D1525 was tested in accordance with JIS K7206The values listed as ASTM D1003 were tested in accordance with JIS K7105The value listed as ASTM E96 was tested in accordance with JIS Z0208Wave Length Absorbing 90% UV Ray, UV Visible Spectrophotometer: 377 nm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

