Emulprene® 1006CR

Emulsion Styrene Butadiene Rubber

INSA

Message:

Description:

E1006CR is a crumb hot emulsion styrene-butadiene copolymer, polymerized using a fatty acid emulsifier and coagulated with salt-acid. It is a very light color product stabilized with a non-staining antioxidant, and presented as free flowing dusted crumb which eliminates the end for size reduction equipment. Between 7% and 12% of Calcium Carbonate is used as dusting agent.

Applications

1.

E1006CR is recommended for light colored applications; for adhesives, tire white sidewalls, transport and transmission belts, sponge materials, sporting goods, flooring, colored shoe soles and heels.

General Information	
Features	Antioxidant
	Copolymer
	High Flow
	Stain Resistant
Uses	Adhesives
	Belts/Belt Repair
	Flooring
	Footwear
	Sporting Goods
	Tires

Physical	Nominal Value	Unit	Test Method
Mooney Viscosity			ASTM D1646
ML 1+4, 100°C ¹	68	MU	
ML 1+4, 100°C	45 to 55	MU	
Ash Content	< 1.0	%	ASTM D5667
Organic Acid	4.0 to 6.0	%	ASTM D5774
Soap	< 0.50	%	ASTM D5774
Styrene Content - Bound	23 to 25	%	ASTM D5775
Volatile Matter	< 0.75	%	ASTM D5668
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	15.6	MPa	ASTM D3185
Tensile Strength	25.0	MPa	ASTM D3185
Tensile Elongation (Break)	450	%	ASTM D3185
NOTE			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

Compound

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



Page 2