

Vidux™ CV-98-P0323-G79 BLACK

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

Vidux™ CV-98-P0323-G79 BLACK is a Flexible Polyvinyl Chloride material. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

Important attributes of Vidux™ CV-98-P0323-G79 BLACK are:

Wear Resistant

Conductive

Flame Retardant

Typical application of Vidux™ CV-98-P0323-G79 BLACK: Hose/Tubing

General Information			
Features	Conductive		
	Flame Retardant		
	Good Abrasion Resistance		
	Good Wear Resistance		
Uses	Tubing		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.26	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	85		
Shore A, 15 sec	79		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	6.89	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Taber Abrasion Resistance (2000 Cycles, 1000 g, H-22 Wheel)	0.410	mg	ASTM D1044
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.2E+2	ohms	ASTM D257
Volume Resistivity	1.4E+2	ohms · cm	ASTM D257
Conductivity	2.0	ohms · cm	ASTM D257

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

