

NEXT SIGNATURE PPH G30-300

Polypropylene Homopolymer

NEXT Specialty Resins, Inc.

Message:

NEXT SIGNATURE PPH G30-300 is a Polypropylene Homopolymer (PP Homopolymer) material filled with 30% glass fiber. It is available in North America. Important attributes of NEXT SIGNATURE PPH G30-300 are:
Good Processability
Homopolymer
Typical application of NEXT SIGNATURE PPH G30-300: Automotive

General Information			
Filler / Reinforcement	Glass Fiber,30% Filler by Weight		
Features	Good Moldability		
	Homopolymer		
Uses	Automotive Applications		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.12	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	95		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	58.6	MPa	ASTM D638
Tensile Elongation (Break)	2.0	%	ASTM D638
Flexural Modulus	4480	MPa	ASTM D790
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	135	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT