Rigidex® P CAP906S

Polypropylene Impact Copolymer INEOS Olefins & Polymers Europe

Message:

Rigidex® P CAP906S is an impact copolymer polypropylene suitable for closures requiring good impact performance, especially at low temperature, balanced with low tendency to stress whitening. It is specifically designed and formulated for bi-component screw caps for carbonated soft drinks made by either injection or compression moulding.

Typical applications

closures requiring good impact performances- especially at low temperature - and easy application and opening torqu

bi-component screw caps for carbonated soft drinks

Benefits and Features

Good processability

High impact strength

Low tendency to exhibit stress whitening

Grade containing slip agent for easy opening

Good mould release

General Information						
Additive	Slip	Slip				
Features	Good Mold Release					
	Good Processability					
	High Impact Resistance					
	Impact Copolymer					
	Low Temperature Impact Resistance					
	Slip					
	Stress Whitening Resistant					
Uses	Caps					
	Closures					
RoHS Compliance	Contact Manufacturer					
Processing Method	Compression Molding					
	Injection Molding					
Physical	Nominal Value	Unit	Test Method			
Melt Mass-Flow Rate (MFR) (230°C/2. kg)	6.0	g/10 min	ISO 1133			
Mechanical	Nominal Value	Unit	Test Method			
Tensile Stress (Yield)	30.0	MPa	ISO 527-2			
Flexural Modulus (23°C)	1500	MPa	ISO 178			
Impact	Nominal Value	Unit	Test Method			
Charpy Notched Impact Strength			ISO 179/1eA			
0°C	4.0	kJ/m²				
23°C	6.0	kJ/m²				

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa,			
Unannealed)	110	°C	ISO 75-2/B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

