

Hostacom TRC 419N C13034

Polypropylene Copolymer

LyondellBasell Industries

Message:

Hostacom TRC 419N C13034 is a high melt flow, 25% mineral filled, UV resistant polypropylene copolymer. The product exhibits a high stiffness, a good impact strength and is equipped with an antistatic package. It is designed for automotive interior applications.

This grade is available in custom colour, pellet form.

General Information			
Filler / Reinforcement	Mineral,25% Filler by Weight		
Additive	Antistatic		
Features	Antistatic		
	Copolymer		
	Good Impact Resistance		
	Good Stiffness		
	Good UV Resistance		
	High Flow		
	Non-Toxic		
Uses	Automotive Interior Parts		
Appearance	Colors Available		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.10	g/cm ³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	2000	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	20	kJ/m ²	ISO 180/1A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT