

Nipolon® Hard 7300

High Density Polyethylene

TOSOH Corporation

Message:

Nipolon® Hard 7300 is a High Density Polyethylene material. It is available in Asia Pacific, Europe, or North America for blow molding, blown film, extrusion, or injection molding.

Important attributes of Nipolon® Hard 7300 are:

- Good Processability
- High Hardness
- High Strength

Typical applications include:

- Containers
- Bags/Liners
- Bottles
- Consumer Goods
- Household Applications

General Information	
Features	Good Processability High Hardness High Tensile Strength
Uses	Bags Bottles Crates Drums Food Packaging Fuel Tanks Household Goods Industrial Containers Netting Toys
Forms	Pellets
Processing Method	Blow Molding Blown Film Extrusion Injection Molding

Thermal	Nominal Value	Unit	Test Method
Melting Temperature	132	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT