

KRATON® G2806 GO-N

Styrene Ethylene Butylene Styrene Block Copolymer

Kraton Polymers LLC

Message:

KRATON® G2806 GO-N is a compound designed for film applications in the Personal Care market.

Kraton G2806 GO-N - supplied as an organic dusted dense pellet

General Information			
Features	Block Copolymer		
Uses	Film		
	Personal Care		
Forms	Pellets		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.870 to 0.910	g/cm ³	Internal Method
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	6.0 to 14	g/10 min	ASTM D1238
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D412
100% Strain	0.689	MPa	
300% Strain	1.24	MPa	
Tensile Strength (Yield)	9.31	MPa	ASTM D412
Tensile Elongation (Break)	1200	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT