

BAAF UHMW-PE M-2

High Density (UHMW) Polyethylene

BAAF

Message:

BAAF UHMW-PE M-2 is a High Density (UHMW) Polyethylene material. It is available in Asia Pacific or Europe.

General Information			
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.935 to 0.940	g/cm ³	Internal Method
Apparent Density			Internal Method
-- ¹	> 0.35	g/cm ³	
-- ²	> 0.38	g/cm ³	
Molecular Weight	2000000 to 3000000		Internal Method
Particle Size ³	> 98.0	%	Internal Method
Volatile Matter	< 0.15	wt%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			Internal Method
Break ⁴	> 32.0	MPa	
Break ⁵	> 34.0	MPa	
Tensile Strain			Internal Method
Break ⁶	300	%	
Break ⁷	350	%	
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength			Internal Method
-- ⁸	> 95	kJ/m ²	
-- ⁹	> 130	kJ/m ²	
Unnotched Izod Impact Strength ¹⁰	No Break		Internal Method
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	> 80.0	°C	Internal Method
NOTE			
1.	M-1 B		
2.	M-1 A		
3.	through 20 mesh sieve		
4.	M-1 B		
5.	M-1 A		
6.	M-1 B		
7.	M-1 A		
8.	M-1 B		

9.	M-1 A
10.	M-1 B

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT