

# Fainplast PVC GK 01596

Polyvinyl Chloride

Fainplast Compounds S.r.l

## Message:

Fainplast PVC GK 01596 is a Polyvinyl Chloride product. It is available in Africa & Middle East, Europe, Latin America, or North America. Typical application: Wire & Cable.

Characteristics include:

Chemical Resistant

Flame Retardant

General Information			
Additive	Flame Retardant		
Features	Hydrocarbon Resistant		
Uses	Cable Jacketing Wire & Cable Applications		
Agency Ratings	NF M 87-202		
Physical	Nominal Value	Unit	Test Method
Density	1.41	g/cm <sup>3</sup>	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	87		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 16.5	MPa	ISO 527-2
Tensile Strain (Break)	> 300	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Thermal Stability	> 50	min	CEI 20-34/3-2
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	29	%	ISO 4589-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

