

Sanren DJ200 (1st-grade)

Low Density Polyethylene

SINOPEC Shanghai Petrochemical Co. Ltd.

Message:

The oblate pellet product is colourless with excellent chemical stability. Under the normal conditions, the product is acid resistant, alkali resistant and salt resistant. It possesses certain mechanical properties and good dielectric characteristics.

Scope of Application: Crosslinked wire and cable compound

General Information			
Features	Low density		
	Homopolymer		
	Good electrical performance		
	alkali resistance		
	acid resistance		
Uses	Wire and cable applications		
Appearance	Colorless		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.922	g/cm³	Internal method
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.6 - 2.4	g/10 min	Internal method
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 11.0	MPa	Internal method
Additional Information	Nominal Value		
Hue			
Cleanliness: <15 pieces/kg			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT