Nipol® NBR DN3380

Acrylonitrile Butadiene Rubber

Zeon Corporation

Message:

Nipol NBR (acrylonitrile butadiene rubber) is a synthetic rubber with extremely well-balanced price, processability, and performance, featuring superior oil resistance and high mechanical strength. Nipol NBR is used in a wide range of applications, including oil resistant hoses, seals, O-rings, rolls, vibration-insulting rubber, and rubber sheets.

ZEON Corporation offers high-quality, high-performance Nipol NBR worldwide as the leading manufacturer of acrylonitrile butadiene rubber.

The next-generation, high efficiency, high performance acrylonitrile butadiene rubber "DN Four Digits Series" features mold contamination resistance, with high-speed vulcanization and high rebound resilience, and was developed to meet a wide variety of needs.

Characteristics & Applications

High cure rate, high modulus, good rebound and well-balanced oil resistance and low temperature resistance.

Fuel hoses, packings, gaskets, oil seals, footwear, printing rolls, and other applications requiring good oil resistance.

General Information	
Additive	Antioxidant 2
Features	Antioxidant
	Fast Cure
	High Strength
	Oil Resistant
Uses	Footwear
	Fuel Lines
	Gaskets
	Rollers
	Seals

Physical	Nominal Value	Unit
Specific Gravity	0.978	g/cm³
Mooney Viscosity	80	MU
Bound Acrylonitrile	33	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

