

Viton® A-601C

Fluoroelastomer

DuPont Performance Elastomers

Message:

Viton® A- 601C is a fluororubber (Fluorelastomer) product. It can be processed by extrusion, compression molding or calendering, and is available in North America or Europe. Viton®The application areas of A- 601C include engineering/industrial accessories and food contact applications. Features include:

- high viscosity
- accessible food
- chemical resistance

General Information	
Features	Solvent resistance Compliance of Food Exposure Viscosity, High
Uses	Washer
Agency Ratings	FDA 21 CFR 177.2600 2
Forms	Sheet
Processing Method	Extrusion Compression molding Calendering

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.81	g/cm ³	ASTM D792
Elastomers	Nominal Value	Unit	Test Method
Compression Set (200°C, 70 hr)	11	%	ASTM D395

Additional Information	
Nominal Viscosity, ML 1 + 10, 121°C: 60Polymer Fluorine Content: 66%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT