Geon[™] Vinyl Flexible HC18080G

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon[™]Vinyl Flexible HC18080G is a flexible polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon[™]Vinyl Flexible HC18080G applications include food contact applications and medical/health care. Features include: accessible food

Radiation resistance

General Information			
Features	Anti-gamma radiation		
	Compliance of Food Exposure		
Uses	Medical devices		
Agency Ratings	FDA Food Exposure, Not Rated		
	FDA not rated		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Extrusion		
	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.23	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹			ASTM D638
Fracture	17.6	MPa	ASTM D638
100% strain	11.0	MPa	ASTM D638
Tensile Elongation ² (Break)	340	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-36.0	°C	ASTM D746
Additional Information			
注释:本化合物配方中所用的全部成分均在美国食品及药物管理局《联邦法规法典》第21章中列出.唯一的限制是,增塑剂"仅用于高含水量食物".本说明 仅为食品及药物管理局清单关于该产品内容的概述.由用户负责确保此化合物适用于其预期应用.			
NOTE			
1.	Type 4, 510mm/min		
2.	Type 4, 510mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

