# NuSil CV-2566

#### Silicone

### **NuSil Technology**

### Message:

Controlled Volatility (CV) Silicone Materials

Silicone's ability to remain elastic at low temperatures and resistant to breakdown at high temperatures offer excellent utility in extraterrestrial environments where materials are repeatedly exposed to extreme temperatures. NuSil's Controlled Volatility (CV) and Ultra Low Outgassing TM (SCV) silicone products are used by leading space programs to provide the much-needed resilient protection they require against contamination and material degradation.

Benefits of Silicone Materials for Space

**Broad Operating Temperature** 

Compensation for CTE Mismatch

Protection Against Atomic Oxygen

**Optically Clear Formulations** 

General Information

Flight Legacy

Comments: Pourable RTV Cure, Primed Lap Shear 500 psi (3.4 MPa)

Features	Low to No Outgassing		
Uses	Adhesives		
	Aerospace Applications		
	Electrical/Electronic Applications		
	Sealants		
Agency Ratings	ASTM E 595		
	NASA SP-R-0022A		
Thermal	Nominal Value	Unit	
CLTE - Flow	3.3E-4	cm/cm/°C	
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 100		
Part B	Mix Ratio by Weight: 0.50		
Additional Information	Nominal Value	Unit	
Cure System	Alkoxy		
Uncured Properties	Nominal Value	Unit	
Color	Red		
Density	1.49	g/cm³	
Viscosity	55	Pa·s	
Curing Time (23°C)	1.7E+2	hr	
Pot Life	180	min	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore A)	55		
Lap Shear Strength <sup>1</sup>	3.45	MPa	

Tensile Strength	6.55	MPa
Tensile Elongation at Break	150	%
Tear Strength	7.01	kN/m
Electric Strength	32	kV/mm
NOTE		

1. Primed with SP-120

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

