Sumikon® PM-9615

Phenolic

Sumitomo Bakelite Co., Ltd.

Message:

Sumikon ® PM-9615 is a phenolic (Phenolic) product. It can be processed by injection molding and is available in North America or Asia Pacific. Sumikon ® PM-9615 applications include the automotive industry and hoses. Features include: high strength Heat resistance

General Information			
Features	High strength		
	Heat resistance, high		
Uses	Parts under the hood of a car		
	Application in Automobile Field		
	Fuel line		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	1.77	g/cm³	ISO 1183
Molding Shrinkage	0.20 - 0.40	%	ISO 294-4
Water Absorption (23°C, 24 hr)	0.060	%	ISO 62
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	120		ISO 2039-2
Mechanical	Nominal Value	Unit	Test Method
Flexural Stress	205	MPa	ISO 178
Compressive Stress	275 - 315	MPa	ISO 604
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	4.4	kJ/m²	ISO 179
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa,	220		100 75 2.1
Unannealed)	220	°C	ISO 75-2/A
CLTE - Flow	2.0E-5	cm/cm/°C	ISO 11359-2
Electrical	Nominal Value	Unit	Test Method
Dielectric Strength	10	kV/mm	IEC 60243-1

Insulation Resistance, JIS K6911, as molded: 1E12 to 1E14 ohmInsulation Resistance, JIS K6911, after boiling: 1E11 to 1E13 ohmAppearance after heating, JIS K6911, @ 2 hrs: 200°CAII ISO values were tested in accordance with JIS specifications.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

