

Devcon Floor Grip™

Epoxy; Epoxide

Devcon

Message:

A 2-component, heavy-duty epoxy compound containing silicon carbide granules for anti-skid protection

Intended Use:

Ideal anti-skid coating used in walkways; ramps; loading docks, and stairs.

Product Features:

Applies at temperatures as low as 40°F

Reduces slipping accidents

Adheres to concrete, wood, steel, brick, aluminum, and wet surfaces

Bonds to damp surfaces

Non-corrosive hardener

General Information			
Filler / Reinforcement	Silicon carbide		
Features	Skid Resistant		
Uses	Coating application		
Appearance	Black		
Physical	Nominal Value	Unit	Test Method
Solid content-by Volume	100	%	
Temperature Resistance			
Dry	121	°C	
Wet	49	°C	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	85		ASTM D2240
Thermoset	Nominal Value	Unit	
Thermoset Components			
	Mixing ratio by weight: 2.8		
Component a	Mixing ratio by capacity: 2.2		
	Mixing ratio by weight: 1.0		
Component B	Mixing ratio by capacity: 1.0		
Pot Life (24°C)	50	min	
Thermoset Mix Viscosity	2000	cP	
Additional Information	Nominal Value	Unit	
Cured 7 days @ 75°F			
Uncured Properties	Nominal Value	Unit	
Curing Time	24	hr	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

