

DAI-EL™ G-7801

Fluoroelastomer

DAIKIN AMERICA, INC.

Message:

DAI-EL G-7801 is a cure-incorporated copolymer with high Mooney viscosity. It is designed especially for compression molding of o-rings, seals and other shapes. It has better mold flow and lower compression set than copolymers of similar Mooney viscosity.

General Information		
Features	Copolymer	
	High Viscosity	
	Low Compression Set	
Uses	Gaskets	
	Seals	
	Tubing	
Appearance	Cream	
	White	
Forms	Slab	
Processing Method	Compression Molding	
Physical	Nominal Value	Unit
Specific Gravity	1.81	g/cm ³
Mooney Viscosity (ML 1+10, 121°C)	66	MU
Fluorine Content	66	%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

