

# Hostalen CRP 100 RESIST S brown

High Density Polyethylene

LyondellBasell Industries

## Message:

Hostalen CRP 100 RESIST S brown is a high density polyethylene (HDPE), brown coloured similar RAL 8023 with light stabilizer and high melt viscosity for identification marking stripes for sewage pipes made from Hostalen CRP 100 RESIST CR black.

It is not intended for medical and pharmaceutical applications.

General Information			
Additive	UV Stabilizer		
Features	High Viscosity		
Uses	Piping		
Appearance	Brown		
Processing Method	Pipe Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.958	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	0.23	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Oxidation Induction Time (210°C)	> 20	min	ISO 11357-6
Extrusion	Nominal Value	Unit	
Melt Temperature	190 to 220	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT