

# Jam PE 23507

Linear Low Density Polyethylene  
Jam Petrochemical Company

### Message:

Jam PE 23507 is a Linear Low Density Polyethylene product. It can be processed by extrusion coating and is available in Africa & Middle East. Typical application: Coating Applications. Primary characteristic: butene comonomer.

General Information			
Features	Butene Comonomer		
Uses	Coating Applications		
Processing Method	Extrusion Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.923	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	7.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, Compression Molded)	15.2	MPa	ASTM D638
Tensile Elongation (Break, Compression Molded)	40	%	ASTM D638
Flexural Modulus (Compression Molded)	550	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	No Break		ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	95.0	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT