

S&E; PVC G-4157E

Polyvinyl Chloride
S&E; Specialty Polymers, LLC

Message:

S & E PVC G-4157E is a polyvinyl chloride product. It can be processed by extrusion molding of profiles and is available in North America. The main characteristics are: beautiful.

General Information			
Features	General		
	Excellent appearance		
Uses	General		
Appearance	Available colors		
	Natural color		
Forms	Particle		
Processing Method	Profile extrusion molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.39	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	60		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	11.5	MPa	ASTM D412
Tensile Strength (Yield)	20.0	MPa	ASTM D412
Tensile Elongation (Break)	300	%	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-20.0	°C	ASTM D746
Additional Information			

Suggested Stock Temperature: 330-350°F

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT