

Geon™ Vinyl Flexible A6DE3

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™ Vinyl Flexible A6DE3 is a Flexible Polyvinyl Chloride product. It can be processed by extrusion or profile extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

Characteristics include:

High Gloss

UV Stabilized

General Information			
Additive	Biocide		
	UV Stabilizer		
Features	High Gloss		
	UV Absorbing		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		
	Profile Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	60		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹			ASTM D638
Break	24.8	MPa	
100% Strain	23.2	MPa	
Tensile Elongation ² (Break)	280	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ³	256	kN/m	ASTM D624
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	7.50	°C	ASTM D746
Injection	Nominal Value	Unit	
Processing (Melt) Temp	193 to 204	°C	
Extrusion	Nominal Value	Unit	
Melt Temperature	182 to 193	°C	
NOTE			
1.	510 mm/min		

2.	510 mm/min
3.	Die C, 510 mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

